Appl. No. 10/517,180 Amdt. Dated October 24, 2008 Reply to Office action of August 25, 2008 Attorney Docket No. P16940-US1 EUS/J/P/08-3377

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

- (Currently Amended) A method for routing a service request in a telecommunication system towards a destination user, the method comprising the steps of:
- a) storing a collection of identifiers related to a first identifier assigned to said user:
  - b) receiving a service request that comprises said first identifier;
- c) obtaining a plurality of identifiers among said collection of identifiers, the identifiers all equally usable for routing said service request:
  - d) selecting a second identifier among said plurality of identifiers; and
  - e) routing said service request according to said selected second identifier; wherein

at least one identifier among said plurality of identifiers stored in step a) has a format that comprises a user-name portion and a domain-name portion, wherein the user-name portion contains said first identifier; and

in step d) said second identifier is selected having a format comprising a username portion and a domain-name portion, wherein said user-name portion contains said first identifier.

- (Original) The method of claim 1, wherein the step c) further comprises the steps of:
- c1) sending a query to a database that contains said collection of identifiers related to said first identifier, said query comprising the content of the first identifier:
- c2) receiving a response to said query that comprises a plurality of identifiers among said collection of identifiers.

Appl. No. 10/517,180 Amdt. Dated October 24, 2008 Reply to Office action of August 25, 2008 Athorney Docket No. P16940-US1 EUS/J/P/08-3377

- (Previously Presented) The method of claims 1, wherein said first identifier is a E.164 number and said second identifier is a Uniform Resource Locator for Session Initiation Protocol
- 4. (Original) The method of claim 3, wherein said second identifier contains number portability information.
- (Currently Amended) An apparatus for routing a service request in a telecommunication system, the apparatus comprising:

communication means arranged for receiving a service request towards a destination user, said service request comprising a first identifier assigned to said destination user:

processing means arranged for obtaining a plurality of identifiers, the plurality of identifiers all equally usable for routing said service request, related to said first identifier and for selecting a second identifier among said plurality of identifiers; and

routing means arranged to route said service request according to said selected second identifier:

## wherein

said processing means are arranged to select a second identifier among said plurality of identifiers having a format that comprises a user-name portion and a domainname portion, wherein said user-name portion contains said first identifier.

- 6. (Currently Amended) A system for routing a service request in a telecommunication system, the system comprising:
- a data base, in charge of storing a collection of identifiers related to a first identifier associated to a user; and
- a serving node of said telecommunication system in charge of receiving a service request towards a destination user and further routing said service request;

said data base being arranged to receive a query comprising the content of said first identifier, and to answer said query with a plurality of identifiers among said Appl. No. 10/517,180 Amdt. Dated October 24, 2008 Reply to Office action of August 25, 2008 Attorney Docket No. P16940-US1 EUS/J/P/08-3377

collection of identifiers, the plurality of identifiers all equally usable for routing said service request:

said serving node being arranged for querying said data base upon reception of a service request that comprises said first identifier, and further routing said service request according to an identifier selected among said plurality of identifiers;

wherein

said serving node is further arranged for routing said service request according to a second identifier selected from among said plurality of identifiers that has a format comprising a user-name portion and a domain-name portion, wherein said user-name portion contains said first identifier.

- (Original) The system of claim 6, wherein said first identifier is a E.164 number and said second identifier is a Uniform Resource Locator for Session Initiation Protocol.
- (Original) The system of claim 7, wherein said wherein said second identifier contains number portability information.